

04-23

mojo®

Made in Germany

KART RACING TYRE

MOJO D1

rear: 5.0 / 11.0 - 5 | **front:** 4.0 / 10.0 - 5

0,80 (± 0,10) bar

11,60 (± 1,45) psi

recommended pressures (cold)

SAFETY WARNING:

- FOR RACING PURPOSE ONLY!
- Max. speed: 140 km/h (87 mph)
- Mount tyres with correct direction of rotation.
- Inflate tyres using a safety cage (Inflation pressure must not exceed 4,0 bar/58 psi).
- Always mount tyre on specified rim only.
- Never use cracked, rusted or deformed rims.
- Use lubricant (tyre paste) when mounting tyre on rim.
- Do not use screwdrivers etc. to mount tyre onto rim.
- Beware the bead locking screws are not protruding through the rim when inflating the tyre.
- Do not store tyres below -10°C (14°F).
- When fitting tyres on rims and initial inflation, tyre temperature must be above +15°C/60°F.
- The use of tyre softeners or tyre treatments of any kind is prohibited.

For more information please visit:
www.rotax-racing.com
www.mojo-tyres.com

© 2026 BRP-Rotax GmbH & Co KG. All rights reserved.
®, TM and the BRP logo are trademarks of Bombardier Recreationcal Products Inc. or its affiliates.